

LIVE TO PLAY LIVE®





92503014462revB



FFM2 GERMANIUM FUZZ FACE® MINI DISTORTION

POWER

The FFM2 is powered by one

9-volt battery (open battery door

on underside of pedal to install).

a 9-volt AC adapter such as the

Dunlop ECB003/ECB003EU, or

a DC Brick[™] power supply.

DESCRIPTION

- · Legendary Fuzz Face tone with pedalboard-friendly size, AC power and on/bypass status LED
- Based on '66-'68 era pre-silicon Fuzz Face pedals
- Warm vintage fuzz tones provided by slightly mismatched germanium transistors
- True bypass

2 1 CONTROLS 1 VOLUME knob controls overall WZZFACA. effect volume 2 FUZZ knob controls amount of fuzz \mathbf{O} 3 FOOTSWITCH toggles on/ · LOLUMA bypass (blue LED indicates on)

DIRECTIONS

- Run a cable from your guitar to the FFM2's INPUT jack and another cable from the FFM2's OUTPUT jack to your amplifier.
- Start with both controls at 12 o'clock.
- · Turn the effect on by depressing the footswitch.
- Botate the VOLUME knob clockwise to increase overall effect volume or counterclockwise to decrease it.
- Botate the FUZZ knob clockwise to increase amount of fuzz or counterclockwise to decrease it.

SPECIFICATIONS

Input Impedance	10 kΩ
Output Impedance Max Volume	2 kΩ
-6 dB Volume	115 kΩ
Max Gain	45 dB
Bypass Current Draw Power Supply	True Hardwire 3.4 mA 9 volts DC



DUNI OP MANUFACTURING, INC. P.O. BOX 846 BENICIA. CA 94510 U.S.A. TEL: 1-707-745-2722 EAX: 1-707-745-2658

